

### Product Overview

	STANDARD INSULATION UNDERLAYS			PREMIUM INSULATION UNDERLAYS			SPECIAL INSULATION UNDERLAYS			
	PAPSILENT	PAPSILENT	PAPSILENT	PAPSILENT	PAPSILENT	PAPSILENT	PAPSILENT	PAPSILENT	PAPSILENT	PAPSILENT
	1200 basic slim	visco basic	visco basic slim	2400 premium	2400 premium alu	visco premium alu	vinyl tile edition	tile edition	professional edition	glue professional
	515P001	515P002	515P003	515P004	515P005	515P006	515P007	515P008	515P009	515P010
Underlay suitable for	All Floorings	All Floorings	All Floorings	All Floorings	All Floorings	All Floorings	Vinyl- and Design Floorings	Tiles and Ceramic Floorings	Parquet and Laminate	All Floorings
Thickness	0.62 mm	2.0 mm	1.0 mm	1.2 mm	1.2 mm	2.0 mm	1.5 mm	3.5 mm	2.9 mm	0.7 mm
Format	0.75 x 13.4 m	0.98 x 15.3 m	1 x 15 m	0.75 x 6.7 m	0.75 x 6.7 m	0.98 x 15.3 m	0.75 x 6.7 m	0.75 x 0.55 m	0.75 x 6.7 m	1 x 10 m
Area	10 m <sup>2</sup>	15 m <sup>2</sup>	15 m <sup>2</sup>	5 m <sup>2</sup>	5 m <sup>2</sup>	15 m <sup>2</sup>	5 m <sup>2</sup>	2.06 m <sup>2</sup>	5 m <sup>2</sup>	10 m <sup>2</sup>
Reduction of impact sound (IS)	19 dB	20 dB	bis 22 dB	21 dB	21 dB	22 dB	22 dB	14 dB	~ 21 dB	19 dB
Reduction of reflected walking sound (RWS)	44%	27%	32%	31%	31%	32%	38%	_	39%	34%
Compressive strength (CS)	> 1,000 kPa	99.3 kPa	129 kPa	> 1,000 kPa	> 1,000 kPa	95.6 kPa	337 kPa	> 1,000 kPa	~ 200 kPa	> 1,000 kPa
Punctual conformability (PC)	0.2 mm	1.4 mm	0.87 mm	0.17 mm	0.17 mm	1.4 mm	0.95 mm	_	2.1 mm	0.26 mm
Water vapour diffusion resistance (SD)	> 75 m	-	-	> 100 m	> 200 m	> 100 m	> 75 m	> 250 m	> 150 m	> 75 m
Thermal resistance (R)	0.003 m <sup>2</sup> K/W	0.0358 m <sup>2</sup> K/W	0.016 m <sup>2</sup> K/W	0.006 m <sup>2</sup> K/W	0.003 m <sup>2</sup> K/W	0.041 m <sup>2</sup> K/W	0.022 m <sup>2</sup> K/W	0.007 m <sup>2</sup> K/W	0.07 m <sup>2</sup> K/W	0.002 m <sup>2</sup> K/W

The technical data was carefully arranged by best knowledge. Listed Dimensions are for guidance only and are therefore stated without tolerances. The product is described in technical respect, but without assurance of characteristics. Customers are not discharged of their liability of goods receipt control. Technical modifications reserved.